



100% FULL-HEAD CARBIDE

Delivers 5X life in concrete with rebar and longer life in all masonry drilling



DIFFUSION-BONDING TECHNOLOGY

High-heat, high pressure solid-state welding process bonds carbide and steel at a molecular level for a stronger bond



4-CUTTER BIT TIP

Provides 180° cutting diameter for increased drilling speed



ACTIVE CENTERING TIP

Provides rounder holes for precisionanchoring applications



FOUR-FLUTE DESIGN

Aggressively pulls dust from the work

USER SCENARIOS

"I'm breaking bits the first time I hit rebar." "I need a concrete bit that lasts."

BOSCH VALUE

- ▶ 5X life in concrete with rebar
- Bosch-made carbide
- ▶ Only 100% carbide head bit available in retail channels

OPTIMAL FOR (TRADES)











MODEL	DIAMETER	DRILLING LENGTH	BIT LENGTH
HCFC5005	3/8 in.	8 in.	13 in.
HCFC5010	1/2 in.	8 in.	13 in.
HCFC5011	1/2 in.	16 in.	21 in.
HCFC5013	1/2 in.	24 in.	29 in.
HCFC5015	9/16 in.	8 in.	13 in.
HCFC5016	9/16 in.	16 in.	21 in.
HCFC5017	9/16 in.	24 in.	29 in.
HCFC5020	5/8 in.	8 in.	13 in.
HCFC5021	5/8 in.	16in.	21 in.
HCFC5023	5/8 in.	31in.	36 in.
HCFC5024	5/8 in.	24in.	29 in.
HCFC5030	3/4 in.	8 in.	13 in.
HCFC5031	3/4 in.	16 in.	21 in.
HCFC5033	3/4 in.	31 in.	36 in.
HCFC5034	3/4 in.	24 in.	29 in.
HCFC5040	7/8 in.	8 in.	13 in.
HCFC5041	7/8 in.	16 in.	21 in.
HCFC5044	7/8 in.	24 in.	29 in.
HCFC5043	7/8 in.	31 in.	36 in.
HCFC5050	1 in.	8 in.	13 in.
HCFC5051	1 in.	16 in.	21 in.
HCFC5053	1 in.	31 in.	36 in.
HCFC5054	1 in.	24 in.	29 in.